

CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8)Applicant(s): **Yoshinori NISHIWAKI et al.**

Docket No.

2002JP314D

Serial No.

10/532,364

Filing Date

April 20, 2005

Examiner

To Be Assigned

Group Art Unit

To Be AssignedInvention: **CHEMICALLY AMPLIFIED POSITIVE PHOTSENSITIVE RESIN COMPOSITION**I hereby certify that this **English Language abstract of JP 62-215947 - 2 Pages***(Identify type of correspondence)*

is being deposited with the United States Postal Service as first class mail in an envelope addressed to: The

Commissioner of Patents and Trademarks, Washington, D.C. 20231-0001 on **September 21, 2005***(Date)***MARIA T. SANCHEZ***(Typed or Printed Name of Person Mailing Correspondence)*
*(Signature of Person Mailing Correspondence)***Note: Each paper must have its own certificate of mailing.**

BEST AVAILABLE COPY

(11)Publication number : **62-215947**

(43)Date of publication of application : 22.09.1987

(51)Int.Cl. G03C 1/72

G03F 7/10


(21)Application number : 61-058150

(71)Applicant : MITSUBISHI CHEM IND LTD
KONISHIROKU PHOTO IND
CO LTD

(22)Date of filing : 18.03.1986

(72)Inventor : URANO TOSHIYOSHI
TOMIYASU HIROSHI
MAEDA YOSHIHIRO
NAKAI HIDEYUKI
GOTO SEI
SASA NOBUMASA

(54) PHOTSENSITIVE COMPOSITION AND PHOTSENSITIVE LITHOGRAPHIC PRINTING PLATE



(57)Abstract:

PURPOSE: To obtain a material for a lithographic printing plate having superior photosensitivity without deteriorating the developability or the suitability to exposure giving a visible image by forming a photosensitive layer contg. a compound producing an acid by exposure and a prescribed compound on a support.

CONSTITUTION: A photosensitive layer of a photosensitive composition contg. a compound producing an acid by exposure and a compound having at least three acetal bonds which are decomposed by the acid in the molecule is formed on a support. Novolak resin represented by formula I (where Ar is an aromatic group, R1 is 2-cyclic ether, each of R2 and R3 is H, alkyl

or phenyl and $n \geq 3$) may be used as the compound having at least three acetal bonds in the molecule. The amount of the compound used is 20W80wt%, preferably 50W60wt%

of the total amount of the solid substances in the photosensitive composition. An alkali-soluble resin such as cresol-formaldehyde resin or phenol-cresol formaldehyde resin may be added to the composition.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]